```
ANSWER 19 OF 24 CA COPYRIGHT 2006 ACS on STN
L6
AN
     122:87744 CA
     Entered STN: 18 Feb 1995
ED
    Admixtures for cement, and cement compositions
TI
     containing the admixtures
     Kyogoku, Yasuhiro; Kanamori, Shinji; Ida, Makio; Mihara, Toshio
IN
     Denki Kagaku Kogyo Kk, Japan
PA
     Jpn. Kokai Tokkyo Koho, 5 pp.
     CODEN: JKXXAF
DT
     Patent
LΑ
     Japanese
IC
     ICM C04B022-12
     ICS C04B022-14; C04B024-26; C04B028-02; C04B028-22
     58-1 (Cement, Concrete, and Related Building Materials)
CC
FAN. CNT 1
                                                                  DATE
     PATENT NO.
                        KIND
                               DATE
                                           APPLICATION NO.
     -----
                        ----
    JP 06256053
                         A2
                               19940913
                                           JP 1993-39922
                                                                  19930301
                               19930301
PRAI JP 1993-39922
CLASS
                CLASS PATENT FAMILY CLASSIFICATION CODES
PATENT NO.
                ----
                       ------
                       C04B022-12
JP 06256053
                ICM
                ICS
                       C04B022-14; C04B024-26; C04B028-02; C04B028-22
                       C04B0022-12 [ICM,5]; C04B0022-14 [ICS,5]; C04B0024-26
                IPCI
                       [ICS,5]; C04B0028-02 [ICS,5]; C04B0028-22 [ICS,5]
AΒ
     Th admixts. contain latent hydraulic binders, Ca fluoroaluminates, inorg.
     sulfates, thickeners, and water reducing agents, and
    are mixed with cement to give the cement compns.
     Concrete prepared from a composition containing portland cement 56,
     fly ash 24, Ca fluoroaluminate 10, and II-type anhydrite
     10 weight parts 460, water 158.1, fine aggregate 889, coarse
    aggregate 741, and Darex Super 100PHX (water reducing
    agent) 6.9 kg/m3, with addition of Me cellulose 20, and air-entraining agent
     23 g/m3, had excellent workability and 3-, 7-, and 28-day compressive
    strength 260, 340, and 480 kg/cm2, resp.
    calcium fluoroaluminate sulfate cement; fly
    ash calcium fluoroaluminate concrete
IT
    Concrete
```

- Cement - flyash - water - water reducing agent